

Grid interactive buildings could get us to net zero

According to the World Green Building Council, construction and operation represents nearly 40% of global energy-related CO₂ emissions today, with a projected 230,000,000,000m² (of new buildings) to be built during the next 40 years. Each of these buildings exists has the potential to actively participate in the energy systems that inhabits.

By [Thabang Byl](#) 25 Aug 2023



GIBs can help reduce greenhouse gas emissions, lower energy costs, and increase grid reliability and resilience. Source: Sueda Dilli/Pexels

Consider the various roads to a net zero future. Building owners and the building industry must take a broader systemic approach, rethinking how it can become active participants in reducing energy consumption.

The good news is the continued move towards building electrification, renewable energy microgrids, energy storage, and digitally automated load control gives building operators the means to become a prosumer.

In a recent [Schneider Electric whitepaper Integrating Smart Building Control Systems to enable GIB](#) it is said these prosumer buildings will produce and consume energy based on real-time conditions of the grid and the operational needs its occupant. These buildings are called Grid Interactive Buildings (GIB).

Simply put, GIBs are structures capable of integrating renewable energy sources such as solar arrays, wind turbines, and energy storage systems into the grid. An all-important feature of GIBs is data generation; these buildings rely heavily on digital metering, controls, and IoT sensor systems that generate relevant data.



AGRICULTURE

Farmers bring arts education to local schools with innovative programme

25 Aug 2023

These network-connected technologies support data processing for decision making and automated controls that are essential in ensuring buildings are in sync with the decision-making real-time conditions of the grid.

GIBs support grid-scale, efficient operations by employing on-site distributed energy resources (DER) and curtailable load. The key to enabling grid interactivity lies in the interoperability between the building management system (BMS), microgrid management system, and electrical power management systems (EPMS).

This interactivity also requires the standardised exchange with grid automation systems such as Advanced Distribution Management Systems (ADMS) and Distributed Energy Resource Management Systems (DERMS).

GIBs can support the grid and the environment

Grids across the world, including South Africa, are under tremendous pressure to deliver building electrification and urbanisation whilst keeping pace with innovation. This pressure can be reduced by utilising buildings that are capable of flexible load operations such as load shedding and load shifting.



Thabang Byl. Source: Supplied

With energy data from power meters and load controls via the BMS, a grid interactive building can shed its load from the grid. The building can opt to compensate by using on-site generation assisted by the microgrid controllers. In turn, this can reduce demand on the grid during peak hours.

Conversely, load shifting is dictated by planned schedules that allow the building to use or power major loads at a different time. For example, if there is a predicted demand charge at 09h00, a building can choose to turn on its heating or cooling systems an hour earlier and allow coasting.

From a carbon footprint perspective, with solar tempering, thermal enveloping, and optimised energy modelling, buildings reduce energy use. For example, by adding solar PV to the roof it can make the building net-zero energy or even net-positive.

Ultimately, GIBs are designed to integrate renewable energy generation sources into the grid, relying heavily on data generation capabilities, digital metering, controls, and IoT sensor systems to process data for decision making and automated controls.

GIBs support grid-scale efficient operations by employing DERs and reduceable loads, and require interoperability between the building management system, microgrid management system, and power management systems for real-time grid interactivity.

ABOUT THE AUTHOR

Thabang Byl is the buildings segment lead at Schneider Electric